



INSULATION(WHITE COLOR)
INSULATION(WHITE COLOR)
INSULATION(BLACK COLOR)
SECTION B-B

Metric thread: M8X0.75
Screw Type connector :
SHEN MING 5.5*2.5DC7.5mmPLUG 655-237

CASE COLOR BLACK.

BAR CODE LABEL

 THIRD ANGLE PROJECTION	DIMENSIONAL TOLERANCES		HOLES : ± 0.05		ANGLES : $\pm 0.5^\circ$	
	() <30 ± 0.2 >30-100 ± 0.3 >100-200 ± 0.4 >200-300 ± 0.5 ABOVE 300 ± 0.6	($\checkmark$) DECIMALS X ± 0.8 XX ± 0.5 XXX ± 0.3	() UP ~ 100 ± 0.2 100-150 ± 0.25 150-200 ± 0.3 200-250 ± 0.35	250-300 ± 0.4 300-350 ± 0.45 350-400 ± 0.5	() UP ~ 600 ± 1.5 600-900 ± 2.4 900-OVER ± 3.1	
SCALE: UNIT: mm						

Functional Ground R/C Type:	R = 1K ohm , C = Not Assembled
Register Number:	C190121002
Switch from:	FSP084-DIBAN2/ 9NA0840527

MODEL NO. : G.P,FSP084-DHAN3(F660006)		TITLE: ASSY		SHEET: 1 OF 1	REV:01
R&D5 Division	P E	DRAWN		DATE	
SEJ	VICTORYU	ANGELH		SEP.03.2020	
INTERIOR COUNTERSIGN:		OAD-00007208		Veronica; Stella	

P/N.:9NA0840736