

電氣規格書



ESD-00000767

FSP075-DHAN3



全漢企業股份有限公司
FSP TECHNOLOGY INC.

台灣桃園市桃園區建國東路22號 統一編號：84239055
No. 22, Jianguo E. Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C)
TEL:+886-3-375-9888 Website:www.FSP-group.com
FAX:+886-3-375-6966 Email:sales@fsp-group.com.tw

Efficiency Testing Criteria

The Product Meet	Regulation	Output Power	Average Efficiency in Active Mode	Maximum Power in No Load
	Department of Energy Level VI	$49W < PO \leq 250W$	$\geq 88\%$	$\leq 0.21W$
	Code of Conduct Tier 2	$49W < PO \leq 250W$	$\geq 89\%$	$\leq 0.15W$



全漢企業股份有限公司
FSP TECHNOLOGY INC.

台灣桃園市桃園區建國東路22號 統一編號：84239055
No. 22, Jianguo E. Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C)
TEL:+886-3-375-9888 Website:www.FSP-group.com
FAX:+886-3-375-6966 Email:sales@fsp-group.com.tw

SPECIFICATION

AC Adapter
FSP075-DHAN3

anticipate IEC 62368-1

P.E	R/D	APPROVED	REV.
Victor	Sej	Shipu	2



Electrical Specification

Electrical Requirements

1. Input Characteristics:

ITEM	CONDITION	SPECIFICATION
1.1 Rated Input Voltage:		100Vac~240Vac
1.2 Input Voltage Range:		90Vac to 264Vac
1.3 Input Frequency Range:		47Hz to 63Hz
1.4 Input Current:	100Vac / Full Load 240Vac / Full Load	$\leq 1.2A$ $\leq 0.7A$
1.5 Input Current Harmonic:		IEC61000-3-2
1.6 Inrush Current:	100Vac,240Vac / Full load(Cold start)	Shall be less than the rating of Adapter critical component (including rectifiers, fuse surge And current limiting device)
1.7 Meet DoE(Level VI):	(1)115Vac / 0A load (2)115Vac / 25%,50%,75%,100% load (Average Active Mode Efficiency , Warm up 30 minutes later)	$\leq 0.21W$ $\geq 88\%$
1.8 Meet CoC(Tier 2):	(1)230Vac / 0A load (2)230Vac / 25%,50%,75%,100% load (Average Active Mode Efficiency , Warm up 30 minutes later)	$\leq 0.15W$ $\geq 89\%$



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

Electrical Requirements

2. Output Characteristics:

※Measured at the end of DC cable.

ITEM	CONDITION	SPECIFICATION
2.1 Output Rated Voltage:		12V
2.2 Output Current:	at constant voltage mode	0A to 6.25A
2.3 Output Voltage Setting:	at the output end of DC cable	12V \pm 5%
2.4 Output Voltage Ripple and Noise: (0.1 μ F Ceramic Cap. and 50V 47 μ F Aluminum Cap. Paralleled between the end of output cable)	115Vac, 230Vac / 0A~6.25A load	\leq 150mVp-p
2.5 Turn-On Delay Time:	At 115Vac /6.25A load, output voltage shall remain regulation	\leq 3Sec
2.6 Hold Up Time:	At 115Vac or 230Vac / 6.25A load, Output voltage shall remain regulation	\geq 10ms
2.7 Rise Time:	At 115Vac / 6.25A load, DC output rise time from 10%~90% of VO	\leq 30ms
2.8 Dynamic Load Change:	(1) Output load step is : (a) 10% ~50 % (b) 50 %~90 % (2) S/R=0.5A/us (3) Frequency is 100Hz & 1KHz	12V \pm 10%
2.9 Overshoot:	115Vac, 230Vac / 0A and 6.25A	12V \pm 10%
2.10 Connector Pin Designations:		Refer to Outline



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

Electrical Requirements

3. Protection Characteristics:

ITEM	CONDITION	SPECIFICATION
3.1 Short Circuit Protection:	When an internal fault occurs, or an external fault is applied to the power supply, such that an overload or short circuit is applied to the output, the power supply shall shut down and enter auto-recovery mode.	Shutdown and no damage
3.2 Over Voltage Protection:	The adapter will enter into shut down that means no output while over voltage happened at output terminal that caused by internal fault, the output trip voltage shall not exceed 18volts. Only internal test.	Shutdown and no damage
3.3 Over Current Protection:	When an internal fault occurs, or an external fault is applied to the power supply, such that an overload is applied to the output, the power supply shall shut down and enter auto-recovery mode. at 115Vac & 230Vac & C. C. Mode	Shutdown and no damage Output current limit : 8A(Max)
3.4 Under-voltage Protection: (Brown Out)	The power supply will enter into shut down while the AC input voltage fall to under normal voltage. That will be return to normal state after the fault has been removed.	Shutdown and no damage



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

Electrical Requirements

4. Environmental Characteristics:


ITEM	CONDITION	SPECIFICATION
4.1 Electric Fast Transients: Refer to IEC61000-4-4	Impulse: $\pm 1\text{kV}$ applied to L,N	Normal operation shall be continued
4.2 Lightning Surge: Refer to IEC61000-4-5	$\pm 1\text{kV}$ applied differential mode	Normal operation shall be continued
	$\pm 2\text{kV}$ applied common mode	Normal operation shall be continued
4.3 Electron Static Discharge: (Refer to IEC61000-4-2 Energy Storage Capacitor 150pF; Discharge Resistor 330 Ω)	Contact Discharge: $\pm 4\text{KV}$ Air Discharge: $\pm 8\text{KV}$	Normal operation shall be continued
4.4 Cooling:	Natural air cooling	
4.5 EMI: Adapter comply with the following national standards: EMI Conducted Emission EMI Radiated Emission	1.Full Load 2. The power supply with internal filter can meet.	FCC PART 15B CLASS B CISPR32 EN55032 CLASS B VCCI LEVEL II
4.6 Safety conforming: 4.6.1 Energy-related Products(ErP) Department of Energy(DoE) Code of Conduct(CoC)		Regulated by customer Comply with ErP standard Comply with DoE standard Code of Conduct(CoC)
4.7 Leakage Current:	264Vac / 50Hz	$\leq 0.25\text{mA}$
4.8 Dielectric Strength: (Hi-Pot)	Between AC input and secondary applied AC 1.5KV / test time 1 minute / cut off current shall be less than 10mA	
4.9 Insulation Resistance	Between AC input and secondary applied DC 500V/ test time 1 second	$\geq 100\text{ M}\Omega$
4.10 Temperature:	Operating	0 to 40°C(Safety) 40 to 70°C Linearly de-rate to 50% load at 70°C , need to check safety with system
	Storage	-20 to +80°C
4.11 Humidity:	Operating	20% ~ 80%
	Storage	10% ~ 90%
4.12 MTBF:	(1) Full Load (2) 230Vac (3) 25°C	300,000Hrs Min. Telcordia SR-332 Issue2



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

Note : Acoustic Noise



Note : Temperature

