

19V AC-ADAPTER F5000-P006

Motherboard Accessories



Supported Motherboard
D3313-Sx/D3543-Sx/D3544-Sx/
D3654-B/D3664-B

FOR



AC adapter w/o mains power cable

- ▶ Input: 100-240 V
- ▶ Output: 19 V/3.42 A (65 W)



POSSIBILITIES START HERE



kontron
S&T Group

► TECHNICAL INFORMATION

PRODUCT FEATURES	INPUT OUTPUT	100-240 V 19 V/3.42 A (65 W)
OPERATING CONDITIONS	TEMPERATURE RANGE HUMIDITY	5 °C - 40 °C 10 % - 90 % relative
APPROVALS		CE, UL, CCC, TÜV/GS, PSE, EAC
RELIABILITY	MTBF	100.000h (25°C)
AC INPUT VOLTAGE	INPUT VOLTAGE RANGE LINE FREQUENCY INPUT HOLD UP TIME EFFICIENCY AC INLET	Nominal: 100 V - 240 V; Min/max: 90 V - 264 V 50 Hz/60 Hz ±5 % ≥ 10 ms @ 115/230 V (nominal load) ≥ 87 % @ 115/230 VAC Socket C8 type
DC OUTPUT	OUTPUT POWER NOMINAL VOLTAGE MIN. / MAX. VOLTAGE MAX. CAPACITIVE LOAD MIN. CURRENT CONTINUOUS CURRENT RIPPLE AND NOISE LPS (LIMITED POWER SOURCE)	65 W 19 V 18.5 V/20 V 1000 µF 0 A 3.42 A max. 350mV (peak to peak) Yes
DIMENSIONS		L: 108.0 mm +/- 0.5 mm W: 46.0 mm +/- 0.5 mm H: 29.5 mm +/- 0.5 mm

► ORDERING INFORMATION

ARTICLE	PART NO.	DESCRIPTION
AC ADAPTER W/O MAINS POWER CABLE	F5000-P006	Delta ADP-65JH AB

► Global Headquarters

Kontron S&T AG

Lise-Meitner-Str. 3-5
86156 Augsburg, Germany
Tel.: + 49 821 4086 0
Fax: + 49 821 4086 111
info@kontron.com
www.kontron.com



Senefelderstr. 8, 41066 Mönchengladbach, Germany
Tel.: +49(0)21 61 - 49 52 6-0, Fax: +49(0)21 61 - 49 52 6 - 29
vertrieb@tps-elektronik.de, www.tps-elektronik.de